

Dimming Compatibility

ID E2308044V0

Product Family: Ogle
Sku Tested: WS-93409
Related Models N/A

Test Voltage: 120V

Control Type: ELV,TRIAC,MLV,0-10V

Test Notes: Refer to dimmer manufacturer's dimmer load rating for min and max fixture quantities per dimmer.

Manufacturer	Product	Model Number	Test Voltage (V)	Measured Dimming Range Low End	Comments				
Adaptive Phase Dimmers									
Control4	Adaptive	C4-APD120	120	30.0%	Flashing at low dimming level				
Legrand	Adorne Touch (ELV)	ADTH700RMTUM1	120	8.0%	Flicker below 8%				
Legrand	Adorne Touch (TRIAC)	ADTH700RMTUM1	120	9.0%	Not Recommended				
Legrand	Radiant	RH703PTUW	120	29.0%	Flashing at low dimming level				
Legrand	Adorne (ELV)	ADTP703TUW4	120	4.0%	Flicker below 4%				
Legrand	Adorne (TRIAC)	ADTP703TUW4	120	4.0%	Not Recommended				
Cooper	AL Series	AAL06	120	18.0%	Flicker below 18%				
Control4	Adaptive	C4-APD277	277	N/A					
Reverse Phase Dimmers (ELV)									
Lutron	Nova T	NTELV-600	120	N/A	Not Recommended/Flashing at highest dimming level				
Lutron	Diva	DVELV-300P	120	3.0%	Flicker below 3%				
Lutron	Maestro	MAELV-600	120	5.0%	Flicker below 5%				
Lutron	Skylark	SELV-300P	120	3.0%	Flicker below 3%				
Leviton	Illumatech	IPE04-1LZ	120	N/A	Not Recommended/Flashing at highest dimming level				
Lutron	Maestro	RRD-6NA	120	5.0%	Flicker below 5%				
Leviton	SureSlide	6615-P0W	120	N/A	Not Recommended/Flashing at highest dimming level				
Leviton	Decora	DSE06-10Z	120	30.0%	Flashing at low dimming level				
Lutron	Caseta	PD-5NE	120	4.0%	Flicker below 4%				
Lutron	Homeworks	HRD-5NE	120	N/A	Flashing at all dimming levels				
Lutron	Homeworks	HQRD-6NA	120	5.0%	Flicker below 5%				
Leviton	Renoir II	AWSMT-EBW	120	30.0%	Flashing at low dimming level				
Lutron	Grafik-Eye	GRX-3103-A-G	120	4.0%	Flicker below 4%				
Leviton	Renoir II	AWSMT-EBW	277	N/A	Flashing at low dimming level				
Lutron	Grafik-Eye	GRX-3103-A-G	277	N/A	Flicker below 4%				
Forward Phase Dimmers (TRIAC)									
Lutron	Maestro	MACL-153M-WH	120	8.0%	Flicker below 8%				
Lutron	Diva	DVCL-153P	120	N/A	Not Recommended/Flashing at highest dimming level				
Legrand	Adorne Paddle	ADPD453LW2	120	N/A	Flashing at all dimming levels				

Perceived light level percentage is the square root of the measured light level percentage, per IESNA Lighting Handbook. This report reflects WAC's test results of a single fixture in single-pole wiring configuration for reference purposes; actual results may vary based on field conditions. Dimmer manufacturers may modify their product at any time, without notice to WAC Lighting, and therefore WAC Lighting cannot ensure future compatibility. For any questions on this report, please contact WAC Lighting Customer Service at 1-800-526-2588 or sales@waclighting.com.



Lutron	Ariadni	AYCL-153PH	120	N/A	Flashing at all dimming levels
		Forward	d Phase Dimmers	(TRIAC) Cont.	•
Lutron	Skylark	SCL-153P-WH	120	N/A	Not Recommended/Flashing at highest dimming level
Lutron	Maestro	MA-600-WH	120	N/A	Not Recommended/Flashing at highest dimming level
Leviton	SureSlide	6674-POW	120	N/A	
Lutron	Caseta	PD-6WCL	120	25.0%	Flashing at low dimming level
Legrand	Harmony	HCL453PW	120	N/A	Flashing at all dimming levels
Legrand	Radiant	RHCL453PW	120	N/A	Flashing at all dimming levels
			0-10V Dimme	ers	
Lutron	Nova T	NTSTV	120	6.0%	Flicker below 6%
Leviton	Decora	IP710-LFZ	120	5.0%	Flicker below 5%
Control4	Adaptive	C4-TV120277	120	6.0%	Flicker below 6%
Lutron	Diva	DVSTV	120	7.0%	Flicker below 7%
Leviton	Renoir	AWSMT-7DW	120	6.0%	Flicker below 6%
Legrand	Radiant	RH4FBL3PW	120	5.0%	Flicker below 5%

Perceived light level percentage is the square root of the measured light level percentage, per IESNA Lighting Handbook. This report reflects WAC's test results of a single fixture in single-pole wiring configuration for reference purposes; actual results may vary based on field conditions. Dimmer manufacturers may modify their product at any time, without notice to WAC Lighting, and therefore WAC Lighting cannot ensure future compatibility. For any questions on this report, please contact WAC Lighting Customer Service at 1-800-526-2588 or sales@waclighting.com.