2" SURFACE INDICATOR QUAD-DIRECTIONAL



2501

LANDSCAPE LIGHTING




Location:

Fixture Type:

Project:

Catalog Number:



PRODUCT DESCRIPTION

LED Landscape surface mount indicator luminaire for both soft and hard ground applications. The indicator light is perfect for outdoor applications, including wells and ponds, decks and patios, inground, as well as ceiling and wall applications.

FEATURES

- Slim low profile design-surface mount installation
- IP68 rated, Suitable for continuous immersion under water
- Factory sealed water tight fi xtures
- · Solid stainless steel construction
- 10' lead wire and direct burial gel filled wire nuts included
- · Maintains constant lumen output against voltage drop
- UL 1838 Listed
- · MLV dimmable with remote MLV dimmer

ORDERING NUMBER

		Color Temp		Finish	
2501	Quad-Directional	27 30	2700K 3000K	BS SS	Bronzed Stainless Steel Stainless Steel

2501-30____

Example: 2501-30SS

SPECIFICATIONS

Input: 9 - 15VAC (Transformer is required)

Power: 2.8W / 3.2 VA (Use VA value for sizing the transformer

and calculate voltage drop.)

Brightness: 4.5ln Beam Angle: 180° CRI: 85

Rated Life: 60,000 hours

waclighting.com Phone (800) 526.2588 Fax (800) 526.2585

Headquarters, East Manufacturing Facility 44 Harbor Park Drive Port Washington, NY 11050 **South East Manufacturing Facility** 1600 Distribution Ct Lithia Springs, GA 30122 **Central Manufacturing Facility** 1700 South J Elmer Freeway, Ste 100 Cedar Hill, TX 75104 West Manufacturing Facility 1750 S Archibald Ave Ontario, CA 91761

1

2" SURFACE INDICATOR QUAD-DIRECTIONAL



2501

LANDSCAPE LIGHTING

Magnetic Transformers



Stainless Steel, 12-15V output, IP65 rated, UL 1838 listed See transformer spec sheet for details and its accessories

9075-TRN-SS 75W Max

9150-TRN-SS 150W Max

9300-TRN-SS 300W Max

9600-TRN-SS 600W Max