GRAND ACCENT 12V
5211

WAC
LANDSCAPE LIGHTING

Fixture Type:

Catalog Number:

Project:

Location:

Ø3⁹⁄₁₆   8¼"   7¼"

PRODUCT DESCRIPTION

Landscape accent luminaire. One fixture replaces all older halogen landscape accent lights

FEATURES

- Adjustable and lockable beam angle
- Integral dimmer
- IP66 rated, Protected against high-pressure water jets
- Includes a detachable shroud
- Solid diecast brass or corrosion resistant aluminum
- Factory sealed water tight fixtures
- 6' lead wire and direct burial gel filled wire nuts
- Maintains constant lumen output against voltage drop
- UL 1838 Listed
- MLV dimmable with remote MLV dimmer

SPECIFICATIONS

Input:	10 - 15VAC (Transformer is required)
Power:	15W to 35W / 21VA - 44VA
Brightness:	740 lm to 2000 lm
Beam Angle:	15° to 60°
CRI:	85
Rated Life:	45,000 hours

ORDERING NUMBER

		Color Temp		Finish	
5211	*Grand Accent 12V*	**27**	*2700K*	**BK**	*Black on Aluminum*
		30	*3000K*	**BZ**	*Bronze on Aluminum*
		40	*4000K*		

5211-_____

Example: **5211-40BK**

waclighting.com
Phone (800) 526.2588
Fax   (800) 526.2585

Headquarters/Eastern Distribution Center
44 Harbor Park Drive
Port Washington, NY 11050

Central Distribution Center
1600 Distribution Ct
Lithia Springs, GA 30122

Western Distribution Center
1750 Archibald Avenue
Ontario, CA 91760

WAC Lighting retains the right to modify the design of our products at any time as part of the company's continuous improvement program. MAR 10 2022

Accessories

Accent Snoot		**5211-SNOOT-BK** **5211-SNOOT-BZ**	*Black on Aluminum* *Bronze on Aluminum*	*Shields lamp and reduces glare*
6" Long Shroud		**5211-LSHR-BK** **5211-LSHR-BZ**	*Black on Aluminum* *Bronze on Aluminum*	*Reduce glare. Ideal for downlighting application*
Additional Stake		**9000-ST9-BZ**	*Bronze*	*Durable PVC stake*
Surface Mount Flange/Stake		**5000-SCP-BZ** **5000-SCP-BBR** **5000-SCP-BK**	*Bronze on Aluminum* *Bronze on Brass* *Black on Aluminum*	*Includes three 7 inch threaded stainless steel stabilizing pins for ground mounting or surface mounts with four screws or over a junction box*
Guardian Mount		**9000-SP9-BZ**	*Stainless Steel*	*Heavy duty stainless steel spike to position fixture* *Formed from a single piece of metal*
Gutter Mount Bracket		**5000-GM-BZ** **5000-GM-BK**	*Stainless Steel*	*Stainless Steel universal mounting bracket for gutter mounting fixture*
Tree Mount Junction Box		**5000-TCP-BZ** **5000-TCP-BK**	*Bronze on Aluminum* *Black on Aluminum*	*Bronze on Aluminum box with Stainless steel mounting screws. Two ½" NPT threaded holes*

Optics

Optics	**LENS-25-AMB**	*Amber*	**LENS-25-BLU**	*Blue* · *Enhances saturation of florals and foliage*
	LENS-25-GRN	*Green*	**LENS-25-FR**	*Frosted*
	LENS-25-RED	*Red*	**5211-HCL**	*Honeycomb Louver*

Extension Rods

Extension Rods	**5000-X04-BZ**	*4 in*	**5000-X18-BZ**	*18 in*	
	5000-X04-BK	*4 in*	**5000-X18-BK**	*18 in*	
	5000-X04-BBR	*4 in*	**5000-X18-BBR**	*18 in*	
	5000-X08-BZ	*8 in*	**5000-X24-BZ**	*24 in*	*Extends distance between Accent light and Surface Mount Canopy, Stake, or Tree Mount box*
	5000-X08-BK	*8 in*	**5000-X24-BK**	*24 in*	
	5000-X08-BBR	*8 in*	**5000-X24-BBR**	*24 in*	
	5000-X12-BZ	*12in*			
	5000-X12-BK	*12 in*			
	5000-X12-BBR	*12 in*			

Rod L-Coupler		**5000-LCO-BZ**	*Bronze*

Magnetic Transformers

Stainless Steel, 12-15V output, IP65 rated, UL 1838 listed
See transformer spec sheet for details and its accessories

9075-TRN-SS	**9150-TRN-SS**	**9300-TRN-SS**	**9600-TRN-SS**
75W Max	*150W Max*	*300W Max*	*600W Max*

WAC Lighting retains the right to modify the design of our products at any time as part of the company's continuous improvement program. MAR 10 2022