


LUCIO – model: LED 6022

W Track System Luminaires



Fixture Type:

Catalog Number:

Project:

Location:

PRODUCT DESCRIPTION

Museum-quality LED luminaire with high performance optics.

FEATURES

- Recessed driver hidden in track
- Accommodates up to 1 lens and 1 glare control accessory
- 365° horizontal aiming and 90° indexed vertical aiming
- Integral selector to choose between independently controllable track circuits
- CBCP intensive ultra spot, 6022U
- Asymmetrical beam distribution, 6022A
- 50,000 rated life
- 5 year warranty

SPECIFICATIONS

- Construction:** Die-cast aluminum body with regressed driver.
- Input:** 120 VAC, 277VAC 50/60Hz
- Power:** 22W
- Light Source:** High output COB LED
- Dimming:** 100%-5% Electronic Low Voltage (ELV), TRIAC
- Standards:** UL & cUL Dry Location Listed, Title 24 JA8-2019 Compliant
- Finish:** Electrostatically powder coated White, Black, Platinum

Track	Model	Beam		Lumens @ 830	CBCP @ 830	Color Temp	CRI	Finish	
WTK WHK	120V 277V	6022	U	8°	1440	35,370	827	2700K	85
			S	12°	1690	15,235	830	3000K	85
			N	20°	1675	8295	835	3500K	85
			F	35°	1650	3730	840	4000K	85
			A	ASY	1755	N/A	927	2700K	90
						930	3000K	90	

- BK** Black
- PT** Platinum
- WT** White



WTK-6022 - _____ - _____

Example: WTK-6022F-827-PT

REPLACEMENT OPTICS

'U' and 'A' are dedicated optics

12°	REF-84BL10-S
20°	REF-84BL10-N
35°	REF-84BL10-F

Accommodates one lens accessory and one glare control accessory. 'U' and 'A' beam fixtures accept one glare control accessory.

LENS ACCESSORIES

Amber	LENS-25-AMB	Frosted Spread Beam Elongating	LENS-25-FR
Blue	LENS-25-BLU		LENS-25-SPR
Green	LENS-25-GRN		LENS-25-BEL
Red	LENS-25-RED		

GLARE CONTROL ACCESSORIES

Cross Louver	LENS-25P-CRL-BK	Snoot	LENS-25-SNOOT-BK
	LENS-25P-CRL-PT		LENS-25-SNOOT-PT
	LENS-25P-CRL-WT		LENS-25-SNOOT-WT
Honey Comb Louver	LENS-25-HCL		

wacighting.com

Phone (800) 526.2588

Fax (800) 526.2585

Headquarters, East Manufacturing Facility

44 Harbor Park Drive

Port Washington, NY 11050

South East Manufacturing Facility

1600 Distribution Ct

Lithia Springs, GA 30122

Central Manufacturing Facility

1700 South J Elmer Freeway, Ste 100

Cedar Hill, TX 75104

West Manufacturing Facility

1750 S Archibald Ave

Ontario, CA 91761

FIXTURE PERFORMANCE

Model #	Beam	Color Temp	Lumens	CBCP	CRI	Model #	Beam	Color Temp	Lumens	CBCP	CRI
WTK-6022U-827 WHK-6022U-827	8°	2700K	1395	33,925	85	WTK-6022F-827 WHK-6022F-827	35°	2700K	1585	3,595	85
WTK-6022U-830 WHK-6022U-830		3000K	1440	35,370	85	WTK-6022F-830 WHK-6022F-830		3000K	1650	3,730	85
WTK-6022U-835 WHK-6022U-835		3500K	1520	35,535	85	WTK-6022F-835 WHK-6022F-835		3500K	1660	3,730	85
WTK-6022U-840 WHK-6022U-840		4000K	1550	35,930	85	WTK-6022F-840 WHK-6022F-840		4000K	1825	4,120	85
WTK-6022U-927 WHK-6022U-927		2700K	1105	26,685	90	WTK-6022F-927 WHK-6022F-927		2700K	1365	3,080	90
WTK-6022U-930 WHK-6022U-930		3000K	1215	29,490	90	WTK-6022F-930 WHK-6022F-930		3000K	1385	3,115	90

Model #	Beam	Color Temp	Lumens	CBCP	CRI	Model #	Beam	Color Temp	Lumens	CBCP	CRI
WTK-6022S-827 WHK-6022S-827	12°	2700K	1625	14,675	85	WTK-6022A-827 WHK-6022A-827	ASY	2700K	1585	N/A	85
WTK-6022S-830 WHK-6022S-830		3000K	1690	15,235	85	WTK-6022A-830 WHK-6022A-830		3000K	1755		85
WTK-6022S-835 WHK-6022S-835		3500K	1680	15,055	85	WTK-6022A-835 WHK-6022A-835		3500K	1840		85
WTK-6022S-840 WHK-6022S-840		4000K	1890	17,030	85	WTK-6022A-840 WHK-6022A-840		4000K	1765		85
WTK-6022S-927 WHK-6022S-927		2700K	1405	12,720	90	WTK-6022A-927 WHK-6022A-927		2700K	1455		90
WTK-6022S-930 WHK-6022S-930		3000K	1415	12,845	90	WTK-6022A-930 WHK-6022A-930		3000K	1430		90

Model #	Beam	Color Temp	Lumens	CBCP	CRI
WTK-6022N-827 WHK-6022N-827	20°	2700K	1605	7,980	85
WTK-6022N-830 WHK-6022N-830		3000K	1675	8,295	85
WTK-6022N-835 WHK-6022N-835		3500K	1670	8,320	85
WTK-6022N-840 WHK-6022N-840		4000K	1865	9,115	85
WTK-6022N-927 WHK-6022N-927		2700K	1380	6,790	90
WTK-6022N-930 WHK-6022N-930		3000K	1400	7,050	90