BALANCE SINGLE LED PATH LIGHT



LANDSCAPE LIGHTING

Fixture Type:	
Catalog Number:	
Project:	
Location:	

PRODUCT DESCRIPTION

Sleek linear design blends seamlessly into pathways while providing soft, even illumination

CDEC	IFICAT	
JELC	IFICAI	IONS.

Input:	9-15VAC (Transformer is required)	
Power:	6.5W / 11.5VA (Use VA value for sizing the transforme	
	and calculate voltage drop.)	
Brightness:	275 lm	
CRI:	90	
Rated Life:	60,000 hours	

FEATURES

- IP66 rated, Protected against powerful water jets
- Factory sealed water tight fixtures
- Solid diecast corrosion resistant aluminum alloy
- Recommended spacing for installation: Residential 11 to 13ft; Commercial: 7 to 9ft
- Mounting stake, 6 foot lead wire, and direct burial gel filled wire nuts are included
- Maintains constant lumen output against voltage drop
- UL & cUL 1838 Listed

ORDERING NUMBER

	Color 1	Color Temp		Finish	
6061 Si	ingle 27	2700K Warm White	BZ	Bronze on Aluminum	
Ba	alance 30	3000K Pure White	BK	Black on Aluminum	

6061-ΒZ

Example: 6061-30BZ

0.1fc 0.2fc 5'9' 1fc 3'8' from the source Avg 4.7fc

waclighting.com Phone (800) 526.2588 (800) 526.2585 Fax

Headquarters, East Manufacturing Facility 44 Harbor Park Drive Port Washington, NY 11050

South East Manufacturing Facility 1600 Distribution Ct Lithia Springs, GA 30122

Central Manufacturing Facility 1700 South J Elmer Freeway, Ste 100 Cedar Hill, TX 75104

West Manufacturing Facility 1750 S Archibald Ave Ontario, CA 91761

6061



BALANCE SINGLE LED PATH LIGHT

6061



Includes three 7 inch threaded stainless steel stabilizing pins for ground mounting or surface mounts with four screws or over a junction box

5000-SCP-BZ Bronze on Aluminum



Guardian Mount

Heavy duty stainless steel spike to position fixture. Formed from a single piece of metal

9000-SP9-BZ Stainless Steel

Magnetic Transformers

Stainless Steel, 12-15V output, IP65 rated, UL 1838 listed See transformer spec sheet for details and its accessories

9075-TRN-SS 75W Max **9150-TRN-SS** 150W Max **9300-TRN-SS** *300W Max* **9600-TRN-SS** 600W Max



Additional Mounting Stake

 $\lambda / A C$

LANDSCAPE LIGHTING



9000-ST9-BK Durable PVC stake

waclighting.com Phone (800) 526.2588 Fax (800) 526.2585

Headquarters, East Manufacturing Facility 44 Harbor Park Drive Port Washington, NY 11050 South East Manufacturing Facility 1600 Distribution Ct Lithia Springs, GA 30122 **Central Manufacturing Facility** 1700 South J Elmer Freeway, Ste 100 Cedar Hill, TX 75104 West Manufacturing Facility 1750 S Archibald Ave Ontario, CA 91761