





Aluminum, ABS

Up to 30°

80"

11 lbs

29W

16° Pitch, 52" sweep

3/4"W X 4.5"H included

UL/cUL Wet Location listed, Energy Star

120 x 12 sensorless DC motor

Up to 150 ft*

Up to 150 ft*

Rated, Title 24 JA8-2016, Title 20 Compliant

SPECIFICATIONS

Mounting Slope:

Hanging Weight:

Total Power:

Standards:

Moter Type:

Wi-Fi Range:

Bluetooth Range:

WIRELESS PERFORMANCE

Construction:

Blade:

Wire:

Downrod:

PRODUCT DESCRIPTION

A smart fan with minimalist appeal. It perfectly suits a range of design styles without overpowering. Convenient wall and remote control options provide flexibility and ease of use, while a whisper-quiet and energy-efficient DC motor powers the ABS blades.

FEATURES

- · 6 fan speeds through both Summer and Winter Modes
- · Silent DC motor
- Includes remote control with wall cradle (RC20-WT)
- Wall control for 3, 4-way control sold separately
- · Compatible with WAC Smart Fans app

AIRFLOW/ENERGY EFFICIENCY Weighed-Average Airflow/High CFM: 4039/5924 Energy Use (W): 21/29 Estimated Yearly Energy Cost (\$): Efficiency (CFM/W): 188 Max RPM: 161

ORDER NUMBER

Model	Housing	Blade
F-003	MB Brushed Aluminum MB Matte Black MW Matte White	TT Titanium Silver MB Matte Black MW Matte White
	SB Soft Brass SB Soft Brass	MW Matte White MB Matte Black

F-003-

Example: F-003-MB

*This fan comes uni-pack - blade select options are not available

*Range results may vary based on application and surroundings.



The WAC app synchronizes seamlessly with smart home devices you already own













waclighting.com Phone (800) 526.2588 (800) 526.2585

Headquarters/Eastern Distribution Center Central Distribution Center 44 Harbor Park Drive Port Washington, NY 11050

1600 Distribution Ct Lithia Springs, GA 30122 Western Distribution Center 1750 Archibald Avenue Ontario, CA 91760

F-003



OPTIONAL ACCESSORIES

OPTIONAL ACCESSORIES				
Bluetooth Wall Control	WC20-	wt	White	Control fan speed and light brightness, and switch between Summer and Winter Modes. Additional Wall Controls can be purchased separately for multiple location control.
Bluetooth Remote Control	RC20-	wT	White	Control fan speed and light brightness, and switch between Summer and Winter Modes. Compatible with WAC Smart Fans. Includes easy-to-install wall cradle and batteries.
Downrod	DR12- 12IN DR18- 18IN DR24- 24IN DR36- 36IN DR48- 48IN DR60- 60IN DR72- 72IN			All our downrods are 1" O.D. and are threaded on the motor end to create an extra layer of security and allow for adjustments in the field.
Downrod Couplers	DC-	BA MB MW SB	Brushed Aluminum Matte Black Matte White Soft Brass	Connects two downrods together.
Sloped Ceiling Kit	SC-			Designed to accommodate buildings with steeper sloped ceilings up to 45° or 12/12 pitch.

Examples: Wall Control - WC20-WT, Remote Control - RC20-WT, Downrod - DR12-BN, Downrod Coupler - DC-MB, Sloped Ceiling Kit - SC-MW

SUGGESTED DOWNROD HEIGHT USAGE

Ceiling Height	15'	14'	13'	12'	11'	10'	9'
Downrod	72"	60"	48"	36"	24"	18"	12"

SLOPED CEILING DEGREE CONVERSION CHART

Degree	4-8°	9-130	14-17o	18-21o	22-25o	26-290	30-320	33-350	36-380	39-41o	42-440	450
Ceiling Slope	1/12	2/12	3/12	4/12	5/12	6/12	7/12	8/12	9/12	10/12	11/12	12/12
Pitch	pitch	pitch	pitch	pitch	pitch	pitch	pitch	pitch	pitch	pitch	pitch	pitch

Supplied mounting brackets allow mounting on ceiling slopes up to 30° (7/12 pitch). Optional slope kit allows mounting on ceilings up to 45° (12/12 pitch). The receiver will mount inside canopy up to 45°.

NOTE: Recommended maximum downrod length of 72" with 80" lead wire