





Aluminum, ABS

Up to 30°

DC 188 x 10

80"

17 lbs

45W

14° Pitch, 54" sweep

3/4"W X 6"H included

UL/cUL Wet Location listed (Damp for SB/MB),

Title 24 JA8-2016, Title 20, Energy Star

Up to 150 ft\* Up to 150 ft\*

LED

20W 2100

90

3000K

Integrated

50,000 hours

**SPECIFICATIONS** 

**Mounting Slope:** 

**Hanging Weight:** 

**Total Power:** 

Standards:

**Motor Type:** 

Wi-Fi Range:

**Light Source: Light Wattage:** 

**Lumens:** 

Dimming:

CRI:

Life:

**Bluetooth Range:** 

**WIRELESS PERFORMANCE** 

**LUMINAIRE PERFORMANCE** 

**Color Temperature: Rated** 

**Construction:** 

Blade:

Wire:

Downrod:

### **PRODUCT DESCRIPTION**

An elegant smart fan with modern allure. Graceful curves and cool refinement are blended with sleek angles and straight lines that result in chic sensibilities and a modern aesthetic. Available in a rich Soft Brass and Matte Black combination or a subdued Matte Black and Distressed Koa.

#### **FEATURES**

- · 6 fan speeds through both Summer and Winter Modes
- · Silent DC motor
- Includes remote control with wall cradle (RC20-WT)
- Wall control for 3, 4-way control sold separately
- · Compatible with WAC Smart Fans app

## **AIRFLOW/ENERGY EFFICIENCY**

Weighted-Average/High Airflow CFM: 4643/6817 Weighted-Average/High Energy Use (W): 17/24 Estimated Yearly Energy Cost (\$): Weighted-Average/High Efficiency (CFM/W): 273/284 Max RPM: 163

### **ORDER NUMBER**

	Model	del Housing			Blade				
	F-054L	SB	Soft Brass	МВ	Matte Black				
		МВ	Matte Black	DK	Distressed Koa				

# F-054L-

Example: F-054L-SB/MB

- \*This fan comes uni-pack blade select options are not available
- \* Range results may vary based on application and surroundings.



The WAC app synchronizes seamlessly with smart home devices you already own













waclighting.com Phone (800) 526.2588 (800) 526.2585

Headquarters/Eastern Distribution Center Central Distribution Center 44 Harbor Park Drive Port Washington, NY 11050

1600 Distribution Ct Lithia Springs, GA 30122 Western Distribution Center 1750 Archibald Avenue Ontario, CA 91760





## **OPTIONAL ACCESSORIES**

OPTIONAL ACCESSORIES							
Bluetooth Wall Control		WC20-	WT	White	Control fan speed and light brightness, and switch between Summer and Winter Modes. Additional Wall Controls can be purchased separately for multiple location control.		
Bluetooth Remote Control	A B V	RC20-	wt	White	Control fan speed and light brightness, and switch between Summer and Winter Modes. Compatible with WAC Smart Fans. Includes easy-to-install wall cradle and batteries.		
Downrod		DR12- 12IN DR18- 18IN DR24- 24IN DR36- 36IN DR48- 48IN DR60- 60IN DR72- 72IN			All our downrods are .75 (in) and are threaded on the motor end to create an extra layer of security and allow for adjustments in the field.		
Downrod Couplers		DC-	BA MB MW OB SB	Brushed Aluminum Matte Black Matte White Oil-Rubbed Bronze Soft Brass	Connects two downrods together.		
Sloped Ceiling Kit	SC-				Designed to accommodate buildings with steeper sloped ceilings up to 450 or 12/12 pitch.		

Examples: Wall Control - WC20-WT, Remote Control - RC20-WT, Downrod - DR12-BN, Downrod Coupler - DC-MB, Sloped Ceiling Kit - SC-MW

## SUGGESTED DOWNROD HEIGHT USAGE

Ceiling Height	15'	14'	13'	12'	11'	10'	9'
Downrod	72"	60"	48"	36"	24"	18"	12"

### SLOPED CEILING DEGREE CONVERSION CHART

Degree	4-8°	9-130	14-17o	18-21o	22-25o	26-290	30-320	33-350	36-380	39-41o	42-440	450
Ceiling Slope	1/12	2/12	3/12	4/12	5/12	6/12	7/12	8/12	9/12	10/12	11/12	12/12
Pitch	pitch	pitch	pitch	pitch	pitch	pitch	pitch	pitch	pitch	pitch	pitch	pitch

Supplied mounting brackets allow mounting on ceiling slopes up to 30° (7/12 pitch). Optional slope kit allows mounting on ceilings up to 45° (12/12 pitch). The receiver will mount inside canopy up to 45°.

NOTE: Recommended maximum downrod length of 72" with 80" lead wire