


# GEOS

F-068L 60"

Ceiling Fan

# WAC SMART FANS



## PRODUCT DESCRIPTION

An otherworldly experience awaits with a silent DC motor so you can hear the leaves rustling outdoors or nothing at all inside. With our WAC Smart Fans app, this fan can integrate with smart home devices you already own, and adaptively learn your desires to schedule its own activity and cut down on energy use.

## FEATURES

- 6 fan speeds through both Summer and Winter Modes
- Silent DC motor
- Luminaire cover not included
- Includes remote control with wall cradle (RC20-WT)
- Wall control for 3, 4-way control sold separately
- Compatible with WAC Smart Fans app

## AIRFLOW/ENERGY EFFICIENCY

<b>Weighted-Average Airflow CFM:</b>	4832/7154
<b>Energy Use (W):</b>	16/18
<b>Estimated Yearly Energy Cost (\$):</b>	4
<b>Efficiency (CFM/W):</b>	301
<b>Max RPM:</b>	145

## ORDER NUMBER

Model	Housing	Blade
F-068L	<b>MB</b> <i>Matte Black</i>	<b>MB</b> <i>Matte Black</i>
	<b>MW</b> <i>Matte White</i>	<b>MW</b> <i>Matte White</i>

## F-068L-\_\_

Example: F-068L-MW

**\*This fan comes uni-pack - blade select options are not available**

**\*Range results may vary based on application and surroundings.**

## SPECIFICATIONS

<b>Construction:</b>	Aluminum, ABS
<b>Blade:</b>	14° Pitch, 60" sweep
<b>Downrod:</b>	3/4"W X 4.5"H included
<b>Mounting Slope:</b>	Up to 30°
<b>Wire:</b>	80"
<b>Hanging Weight:</b>	19 lbs
<b>Total Power:</b>	37.5W
<b>Standards:</b>	UL/cUL Wet Location listed, Title 24 JA8-2016, Title 20 Compliant
<b>Motor Type:</b>	120 x 15 sensorless DC motor

## WIRELESS PERFORMANCE

<b>Wi-Fi Range:</b>	Up to 150 ft*
<b>Bluetooth Range:</b>	Up to 150 ft*

## LUMINAIRE PERFORMANCE

<b>Light Source:</b>	LED
<b>Light Wattage:</b>	19.5W
<b>Lumens/Delivered Lumens:</b>	1600/1025
<b>Dimming:</b>	Integrated
<b>CRI:</b>	90
<b>Color Temperature:</b>	3000K
<b>Rated Life:</b>	50,000 hours

The WAC app synchronizes seamlessly with smart home devices you already own



wacighting.com  
Phone (800) 526.2588  
Fax (800) 526.2585

Headquarters/Eastern Distribution Center  
44 Harbor Park Drive  
Port Washington, NY 11050

Central Distribution Center  
1600 Distribution Ct  
Lithia Springs, GA 30122

Western Distribution Center  
1750 Archibald Avenue  
Ontario, CA 91760

# GEOS

F-068L 60"

Ceiling Fan

# WAC

SMART FANS

## OPTIONAL ACCESSORIES

<p>Bluetooth Wall Control</p>		<p><b>WC20-</b></p>	<p><b>WT</b> White</p>	<p>Control fan speed and light brightness, and switch between Summer and Winter Modes. Additional Wall Controls can be purchased separately for multiple location control.</p>
<p>Bluetooth Remote Control</p>		<p><b>RC20-</b></p>	<p><b>WT</b> White</p>	<p>Control fan speed and light brightness, and switch between Summer and Winter Modes. Compatible with WAC Smart Fans. Includes easy-to-install wall cradle and batteries.</p>
<p>Downrod</p>		<p><b>DR12-</b> 12IN  <b>DR18-</b> 18IN  <b>DR24-</b> 24IN  <b>DR36-</b> 36IN  <b>DR48-</b> 48IN  <b>DR60-</b> 60IN  <b>DR72-</b> 72IN</p>		<p>All our downrods are 1" O.D. and are threaded on the motor end to create an extra layer of security and allow for adjustments in the field.</p>
<p>Downrod Couplers</p>		<p><b>DC-</b></p>	<p><b>BA</b> Brushed Aluminum  <b>MB</b> Matte Black  <b>MW</b> Matte White  <b>SB</b> Soft Brass</p>	<p>Connects two downrods together.</p>
<p>Sloped Ceiling Kit</p>		<p><b>SC-</b></p>		<p>Designed to accommodate buildings with steeper sloped ceilings up to 45° or 12/12 pitch.</p>

Examples: Wall Control - **WC20-WT**, Remote Control - **RC20-WT**, Downrod - **DR12-BN**, Downrod Coupler - **DC-MB**, Sloped Ceiling Kit - **SC-MW**

## SUGGESTED DOWNROD HEIGHT USAGE

Ceiling Height	15'	14'	13'	12'	11'	10'	9'
Downrod	72"	60"	48"	36"	24"	18"	12"

## SLOPED CEILING DEGREE CONVERSION CHART

Degree	4-8°	9-13o	14-17o	18-21o	22-25o	26-29o	30-32o	33-35o	36-38o	39-41o	42-44o	45o
Ceiling Slope	1/12	2/12	3/12	4/12	5/12	6/12	7/12	8/12	9/12	10/12	11/12	12/12
Pitch	pitch	pitch	pitch	pitch	pitch	pitch	pitch	pitch	pitch	pitch	pitch	pitch

Supplied mounting brackets allow mounting on ceiling slopes up to 30° (7/12 pitch). Optional slope kit allows mounting on ceilings up to 45° (12/12 pitch). The receiver will mount inside canopy up to 45°.

**NOTE:** Recommended maximum downrod length of 72" with 80" lead wire