
54" Ceiling Fan







PRODUCT DESCRIPTION

Sensual and intriguing, the SWIRL Smart Fan by WAC is highlighted with a unique blade shape and design. This Energy Star rated creates a unique impression with the stunning geometric three-blade design while offering comfortable air circulation throughout your home.

FEATURES

- 6 fan speeds through both Summer and Winter Modes
- · Silent DC motor
- · Luminaire cover not included
- Includes remote control with wall cradle (RC20-WT)
- · Wall control for 3, 4-way control sold separately
- Compatible with WAC Smart Fans app

AIRFLOW/ENERGY EFFICIENCY

Weighted-Average/High Airflow CFM: 3687/5650 Weighted-Average/High Energy Use (W): 25/36 Estimated Yearly Energy Cost (\$): Weighted-Average/High Efficiency (CFM/W): 191 Max RPM: 162

ORDER NUMBER

Model	Hous	ing	Blade	Blade			
	МВ	Matte Black	DK	Distressed Koa			
F-074L	МВ	Matte Black	МВ	Matte Black			
	SB	Soft Brass	МВ	Matte Black			

F-074L-

Example: F-074L-MB

*This fan comes uni-pack - blade select options are not available

SPECIFICATIONS

Construction: Aluminum, ABS Blade: 24° Pitch, 54" sweep Downrod: 3/4"W X 4.5"H included

Mounting Slope: Up to 30° Wire: 80" **Hanging Weight:** 17 lbs 56W **Total Power:**

Standards: UL/cUL Wet Location listed, Title 24 JA8-2016,

Title 20, Energy Star

Motor Type: DC 120 x D-15

WIRELESS PERFORMANCE

Wi-Fi Range: Up to 150 ft* Up to 150 ft* **Bluetooth Range:**

LUMINAIRE PERFORMANCE

LED **Light Source: Light Wattage:** 19.5W Lumens/Delivered: 1600/1069 Dimming: Integrated CRI: 90 **Color Temperature: Rated** 3000K Life: 50,000 hours

The WAC app synchronizes seamlessly with smart home devices you already own













waclighting.com Phone (800) 526.2588 (800) 526.2585

Headquarters/Eastern Distribution Center Central Distribution Center 44 Harbor Park Drive Port Washington, NY 11050

1600 Distribution Ct Lithia Springs, GA 30122 Western Distribution Center 1750 Archibald Avenue Ontario, CA 91760

^{*} Range results may vary based on application and surroundings.





OPTIONAL ACCESSORIES

OPTIONAL ACCESSORIES			
Bluetooth Wall Control	WC20-	WT White	Control fan speed and light brightness, and switch between Summer and Winter Modes. Additional Wall Controls can be purchased separately for multiple location control.
Bluetooth Remote Control	RC20-	WT White	Control fan speed and light brightness, and switch between Summer and Winter Modes. Compatible with WAC Smart Fans. Includes easy-to-install wall cradle and batteries.
Downrod	DR12- 12IN DR18- 18IN DR24- 24IN DR36- 36IN DR48- 48IN DR60- 60IN DR72- 72IN		All our downrods are .75 (in) and are threaded on the motor end to create an extra layer of security and allow for adjustments in the field.
Downrod Couplers	DC-	MB Matte Black MW Matte White SB Soft Brass	Connects two downrods together.
Sloped Ceiling Kit	SC-		Designed to accommodate buildings with steeper sloped ceilings up to 450 or 12/12 pitch.

Examples: Wall Control - WC20-WT, Remote Control - RC20-WT, Downrod - DR12-MB, Downrod Coupler - DC-SB, Sloped Ceiling Kit - SC-MB

SUGGESTED DOWNROD HEIGHT USAGE

Ceiling Height	15'	14'	13'	12'	11'	10'	9'
Downrod	72"	60"	48"	36"	24"	18"	12"

SLOPED CEILING DEGREE CONVERSION CHART

Degree	4-8°	9-130	14-17o	18-21o	22-25o	26-290	30-320	33-350	36-380	39-41o	42-440	450
Ceiling Slope	1/12	2/12	3/12	4/12	5/12	6/12	7/12	8/12	9/12	10/12	11/12	12/12
Pitch	pitch	pitch	pitch	pitch	pitch	pitch	pitch	pitch	pitch	pitch	pitch	pitch

Supplied mounting brackets allow mounting on ceiling slopes up to 30° (7/12 pitch). Optional slope kit allows mounting on ceilings up to 45° (12/12 pitch). The receiver will mount inside canopy up to 45°.

NOTE: Recommended maximum downrod length of 72" with 80" lead wire