


MT-3LD211 - 2 Lights

Mini LED Multiple Spots



Fixture Type:

Catalog Number:

Project: _____

Location: _____

PRODUCT DESCRIPTION

Integral housing adjustable recessed spot light.

FEATURES

- Individually adjustable luminaires
- Complete unit includes housing & trim
- All housings are Non-IC rated
- 30° visual cutoff for glare control
- 25° vertical tilt and 350° horizontal rotation

SPECIFICATIONS

- Construction:** Die-cast aluminum heat sink painted black. Trim, housing and junction box are 20 gauge steel. Frame and hanger bars are heavy gauge galvanized steel.
- J-Box (New Construction):** Seven knockouts and four Romex® style wiring connectors provided for ease of installation. Rated for branch wiring.
- Driver:** 120VAC Input
- Light Source:** High output LED (included with housing)
- Dimming:** Dim to 5% with electronic low voltage (ELV) dimmer.
- Mounting:** Supplied with hanger bars, adjustable from 14 1/2"-25" to accommodate various joist construction and grid sizes. Hanger bars include a captive mounting "screw-nail" for ease of installation. Accommodates surface up to 1" thick. 8 1/8" x 4 1/8" cutout.
- Finish:** Abrasion resistant powder coat paint
- Standards:** ETL & cETL Damp Location listed; Energy Star rated

Trims (Order Housing and Power Supply Separately)	Model	Power	Beam	Color Temp	CRI	Lumens	CBCP	Finishes
	MT-3LD211NA New Construction Non-IC, Airtight	22W	F 25°	927 2700K	90	870 x 2	2895 x 2	BK White trim with black interior
				930 3000K		900 x 2	3010 x 2	WT White trim with white interior
				935 3500K		935 x 2	3130 x 2	
				940 4000K		965 x 2	3215 x 2	
	MT-3LD211R Remodel Non-IC	22W	F 25°	927 2700K	90	870 x 2	2895 x 2	BK White trim with black interior
				930 3000K		900 x 2	3010 x 2	WT White trim with white interior
				935 3500K		935 x 2	3130 x 2	
				940 4000K		965 x 2	3215 x 2	
	MT-3LD211R Remodel Non-IC	22W	W 45°	927 2700K	90	855 x 2	1200 x 2	BK White trim with black interior
				930 3000K		885 x 2	1250 x 2	WT White trim with white interior
				935 3500K		920 x 2	1295 x 2	
				940 4000K		945 x 2	1330 x 2	

-

Example: **MT-3LD211R-F30-BK**