

OCULARC 3.0 DIM-TO-WARM

Open Reflector - R3BRD, R3BSD

WAC



Fixture Type:

Catalog Number:

Project:

Location:

PRODUCT DESCRIPTION

The brilliant LED recessed downlight that gradually changes to a warmer color temperature as you dim. Great for new construction projects or remodels.

FEATURES

- Dim-to-Warm color temperature range: 3000K - 1800K
- Energy Star® Rated
- Title 24 Compliant
- IC-rated Remodel and New Construction
- Airtight in New Construction and remodel
- Shallow housing under 4" depth
- Cutout 4¼"

SPECIFICATIONS

Construction: Die-cast aluminum trim and heat sink

Dimming: ELV or TRIAC or 0-10V dimming compatible

Input: 120V for R3BNICA-10, R3BBRT-10; 120-277V for R3BNICA-10U

Light Source: 11W 95 CRI Single LED Module. Rated Life: 50,000 hours


Mounting: Retention clips firmly hold trim to housing.

Finish: Powder coated

Ceiling thickness: ½" - 1"

Standards: ETL&cETL listed, Wet location listed

Operating Temperature: -4°F to 104°F (20°C to 40°C)



Trims (Order Housing Separately)	Model	Beam	Max Lumens	Max CBCP	Color Temp	Finish
	R3BRD Round Open Reflector Wet Location Listed	S 19° N 27° F 50°	765	3070	WD 3000K - 1800K	WT White BK Black
	R3BSD Square Open Reflector Wet Location Listed	S 19° N 27° F 50°	735	2850	WD 3000K - 1800K	WT White BK Black

R3BRD-__WD-WT

Example: R3BRD-SWD-WT

wacighting.com

Phone (800) 526.2588

Fax (800) 526.2585

Headquarters, East Manufacturing Facility

44 Harbor Park Drive

Port Washington, NY 11050

South East Manufacturing Facility

1600 Distribution Ct

Lithia Springs, GA 30122

Central Manufacturing Facility

1700 South J Elmer Freeway, Ste 100

Cedar Hill, TX 75104

West Manufacturing Facility

1750 S Archibald Ave



Ontario, CA 91761

OCULARC 3.0 DIM-TO-WARM

Open Reflector - R3BRD, R3BSD



Housings (Required) - Order separately from trims

	Model	Input	Dimming	Notes
<p><i>New Construction</i></p>  <p>12¹/₁₆" 3¹³/₁₆" 7¹/₁₆" 1¹/₈" 10" - 3³/₁₆" 6⁷/₁₆" Ø4¹/₈" 14¹/₂" min 24¹/₂" max</p>	<p>R3BNICA-10 IC-Rated, Airtight</p>	120V	100% - 5% TRIAC, ELV, 0-10V	Less than 4" plenum depth
	<p>R3BNICA-10U IC-Rated, Airtight</p>	120V - 277V	<p>120V 100% - 5% TRIAC, ELV, 0-10V</p> <p>277V 100% - 1% 0-10V</p>	<p>Allows adjustment in any direction when used with adjustable trims</p> <p>Ceiling thickness: 1/2" - 1"</p>
<p><i>Remodel</i></p>  <p>11max" 5¹/₂" 2¹/₁₆"</p>	<p>R3BBRT-10 IC Rated</p>	120V	100% - 5% TRIAC, ELV, 0-10V	<p>Allows adjustment in any direction when used with adjustable trims</p> <p>Ceiling thickness: 1/2" - 1"</p>

Example: **R3BNICA-10**

wacighting.com

Phone (800) 526.2588

Fax (800) 526.2585

Headquarters, East Manufacturing Facility

44 Harbor Park Drive

Port Washington, NY 11050

South East Manufacturing Facility

1600 Distribution Ct

Lithia Springs, GA 30122

Central Manufacturing Facility

1700 South J Elmer Freeway, Ste 100

Cedar Hill, TX 75104

West Manufacturing Facility

1750 S Archibald Ave

Ontario, CA 91761