### **OCULARC 3.5 DIM-TO-WARM**

Wall Wash - R3CSWT, R3CSWL

# WAC LIGHTING





| Fixture Type:   |  |
|-----------------|--|
|                 |  |
| Catalog Number: |  |
| Project:        |  |
| Location:       |  |

# 

#### PRODUCT DESCRIPTION

The brilliant LED recessed downlight that gradually changes to a warmer color temperature as you dim. Great for new construction projects or remodels.

#### **FEATURES**

- 2 beam angle options included:
   Narrow flood beam pre-installed is optimal optic for wall wash
- Non IC and IC-Rated, Airtight, New Construction, Remodel
- Adjustable LED light engine included with housing: Wall Wash Vertical Adjustment to 15°
- Shallow housing under 4" depth
- 5 year warranty

#### **SPECIFICATIONS**

Construction: Die-cast aluminum trim and heat sink Input Power: 13W/16W, 120V-277V 50/60Hz

**Dimming:** 100% - 1% TRIAC, ELV

100% - 5%, 0-10V

**Light Source:** CRI 95 high output COB LED rated life of 50,000 hours

**Mounting:** Retention clips firmly hold trim to housing. Cutout 41/4"x41/4"

**Finish:** Powder coated white, haze.

Ceiling thickness: 1/2" - 1"

**Operating Temp:**  $-4^{\circ}F$  to  $104^{\circ}F$  ( $-20^{\circ}C$  to  $40^{\circ}C$ )

Standards: UL & cUL, Wet Location listed, Title 24 JA8-2019 Compliant

| Trims (Order Housing Separately)                 | Model   | Power | Beam            | Color Temp | Max Lumens | Мах СВСР | Finish |                     |
|--|---|-------|-----------------|------------|------------|----------|--------|---------------------|
| 43/4" —  | <b>R3CSWT</b><br>Square Trim<br>Wall Wash Downlight | 13W   | Asym            |            | 610        | N/A      | WT     | White<br>Haze/White |
| 33%"   |   | 16W   | Asym            |            | 720        | N/A      | BK     | Black               |
| R3CSWL Square Trimless 33/8" Wall Wash Downlight | 13W   | Asym  | - 3000K - 1800K | 610        | N/A        | WT<br>HZ | White  |                     |
|  | 16W   | Asym  |                 | 720        | N/A        | вк       | Black  |                     |

Example: R3CSWL-HZ

**waclighting.com** Phone (800) 526.2588 Fax (800) 526.2585 **Headquarters/Eastern Distribution Center** 44 Harbor Park Drive Port Washington, NY 11050 Central Distribution Center 1600 Distribution Ct Lithia Springs, GA 30122 **Western Distribution Center** 1750 Archibald Avenue Ontario, CA 91760

## **OCULARC 3.5 DIM-TO-WARM**

# Adjustable Downlight - R3CSWT, R3CSWL



| Housing (Required) - Order separately from trims   | Model                            | Power |      | Color Temp  |
|--|----------------------------------|-------|------|-------------|
| 1211/6" — 1211/6 | R3CSN-13<br>IC-Rated Airtight    | 13W   | WD   | 3000K-1800K |
| 313/16" 67/16" 9½" min 24½" max  | <b>R3CSN-16</b> Non IC Airtight  | 16W   |      |             |
| Remodel Trim  11" MAX  4½"  25/8" 33/4"  □ 15/8" 23/16"  | R3CSR-16<br>Non IC<br>Airtight   | 16W   | WD   | 3000K-1800K |
| 8 Remodel Trimless  11" MAX  53/16"  51/2"  51/2"  53/16"  | <b>R3CSRL-16</b> Non IC Airtight | 16W   | **** |             |

R3CS\_\_\_-\_-WD
Example: R3CSN-13-WD